

## H. 最大移动速度和最大长度

KM系列受到滚珠丝杆的危险转速和DN值的限制，其各规格之最大移动速度如下所示。

单位：mm

型号	丝杆导程	轨道长度	最大移动速度(mm/s)			最大长度		
			普通级 N	高级 H	精密级 P	普通级 N	高级 H	精密级 P
KM 26	2	150	280	280	280	300	300	300
		200						
		250						
		300						
	6	150	590	590	830	300	300	300
		200						
KM 30	5	150	390	390	550	600	600	600
		200						
		300						
		400						
		500						
	600	340	340	340	600	600	600	
	10	150	790	790				1100
		200						
		300						980
		400						
500								
600	650	650	650					
KM 33	5	150	390	390	550	600	600	600
		200						
		300						
		400						
		500						
	600	340	340	340	600	600	600	
	10	150	790	790				1100
		200						
		300						980
		400						
500								
600	650	650	650					

型号	丝杆导程	轨道长度	最大移动速度(mm/s)			最大长度			
			普通级 N	高级 H	精密级 P	普通级 N	高级 H	精密级 P	
KM 45	10	340	520	520	740	940	940	740	
		440							
		540							
		640							
		740			730				
	940	430	430	-					
	20	340	1050	1050	1480	940	940	740	
		440							
		540							
		640							
740		1440							
940	840	840	-						
KM 46	10	340	520	520	740	940	940	740	
		440							
		540							
		640							
		740			730				
	940	430	430	-					
	20	340	1050	1050	1480	940	940	740	
		440							
		540							
		640							
740		1440							
940	840	840	-						
KM 55	20	980	800	800	1120	1380	1380	1180	
		1080			900				
		1180			740				740
		1280			620				620
		1380			530				530
KM 65	25	980	800	800	1120	1680	1680	1380	
		1180			830				
		1380							
		1680			550				500